

BB15A

KDS Bump bar

FENGYU





BB15A

KDS Bump bar

Main Features

- 15 Key Sealed Membrane Input Surface
- Interfaces With Current Kitchen Video System
- Tuff-Key Technology
- High Quality and Durable
- Easy Installation
- Relegendable Quick and Easy to Change
- Mechanical Key Switches for Dependable, Durable Operation
- Splash / Spill Proof Design - Provides Protection to its Components
- Standard and Custom Mounting Solutions Available
- Top or Side Mounting Antenna Configuration
- 50 Million Actuations Per Key

Technical Specification

[Electronics]

USB interface

Power supply: +5V/DC $\pm 5\%$

Current input: < 100mA

MTBF: 50,000 hours

RF interface

Input voltage: 2V to 3V

Working current: 5mA

Sleeping current: 30uA

[Mechanical]

Total travel: 1 – 0.2mm

Peak load before make: 14 - 16 Oz

[Customization]

- Color
- Legends
- Interfaces
- Company Logos
- More Available Upon Request

[Others]

Storage temperature: -40°C to +70°C

Operating temperature: 0°C to +70°C

Operating humidity: 20% to 90%

Dimensions: 253 x 75 x 27, mm

- Heng Yu Technology (HK) Limited
- <http://www.hengyu-tech.com>