


DP101C

10" POS Display



FENGYU



Main Features

- Sealed zero-bezel design and full metal housing
- Support HD (1280 x 800) resolution
- Available in VGA, HDMI, USB interface
- Multilingual OSD Menu, with 5-UI buttons
- Support VESA mounting

Technical Specification

[Panel Spec]

Main Display Resolution: 10.1" inches (1280 x 800)

Active Area: 216.96(W) x 135.6(H)



Contrast Ratio: 800

Luminance: 300 cd/m²

Response Time: 30ms

Viewing Angle: 85°/ 85°/ 85°/ 85° (Up/ Down/ Left/ Right)

Touch Panel: PCAP multiple touch (10 points), optional



[Electrical]

[USB interface]

Power Input: USB 5V

Current: 1A

Driver: DisplayLink

Cable Length: 1.8m (2 x USB-A to USB-B /C)

[HDMI / VGA interface]

Power Input: DC 12V 2A

Current: 1A

Cable Length: Standard VGA / HDMI cable, Length 1800mm

[Others]

Storage Temperature: -20°C ~ 70°C

Operating Temperature: 0°C ~ 60°C

Operating Humidity: 10% ~ 80%

Mounting: VESA compliant (100mm x 100mm)

Stands: DZ-004/ DZ-008

Dimensions: 254 x 179 x 38, mm

HENGYU

Heng Yu Technology (HK) Limited
<http://www.hengyu-tech.com>