

# KDS-238GP

# Kitchen Display Terminal

ЕНГҮҮ



# KDS-238GP

**Kitchen Display Terminal**

**HENGYU**

## Main Features

- 23.8" AIO terminals designed for kitchen and other rugged environment
- Robust display made of tempered glass
- Fanless system in a robust metal housing. High-quality electronics industrial components for absolute reliability
- Sealed cable SR design with female connector plugs allows easy extension of the cable length.
- Unused cables can be taken off easily from the sealed cable compartments
- Support several Intel CPU platforms, Celeron, i3-Core , i5-Core and i7-Core
- Clear and bright touch display, intuitive to operate. Full functionality even with wet fingers or latex gloves
- 100 % resistant to water and grease vapor as well as food acids.
- 100 % hygienic thanks to smooth surfaces and edgeless design.
- Can come with optional Heng Yu Kitchen Display software
- Can be equipped with Heng Yu bumpbars

## KDS-238GP-12thCPU Windows System

Features	Model	KDS-238GP-N97	KDS-238GP-SI3	KDS-238GP-SI5		
Processor	CPU	Intel® Alder Lake-N Series Processor	Intel® 12th i3-1215U	Intel® 12th i5-1235U		
	Number of Core	4E	2P4E	2P8E		
	Frequency	Up to 3.60GHz	Up to 4.4GHz/3.3GHz	Up to 4.4GHz/3.3GHz		
Memory	Technology	Support DDR4 3200MHz, 1*non-ECC SO-DIMM Slot				
	Max. Capacity	Up to 32GB				
Display	Controller	Intel UHD Graphics	Intel UHD Graphics	Intel Iris Xe Graphics		
	Graphic Memory	Up to 24 EU, 1.20Ghz	Up to 64 EU, 1.10 GHz	Up to 80 Eus, 1.20 GHz		
	Main Display Resolution	23.8" (1920 x 1080), ratio 16:9				
	Active Area	527.04 x 296.46(mm)				
	Luminance	250cd/m2				
	Viewing Angle (R/ L/ U/ B)	89/ 89/ 89/ 89				
	Touch Panel	P-CAP multiple touch (Max.10 points), optional				
Ethernet	Controller	Realtek GBE LAN Chip (RJ45, 10/100/1000 Mbps)				
Storage	Primary	M.2 (NGFF) Key B/B+M Slot (SATA SSD, 2280)	M.2 (NGFF) PCIe4 Key M Slot (NVME SSD, 2280)			
I/O Interface	Main USB	4 x USB-A 3.0				
	Audio	Line-Out/ Mic 3.5mm Jack				
	Serial	DB9 x 1				
	LAN	RJ45 / POE++ LAN (Optional)				
Options	Bumpbar	BB20A / MK15F / USB Speaker				
Power Adaptor	Input	Universal AC 100~240V, 50/60 Hz				
	Output	DC +12V 5A/ Support POE++ power (Optional)				
Environment	Storage Temperature	-15°C ~ 55°C				
	Operation Temperature	-0°C ~ 40°C				
	Operation Humidity	10% ~ 85%				
Mounting	Standard	VESA Mount 200 x 200 (mm)				
Dimension	Panel (w/o stand)	574 x 344 x 60 (mm)				