









# Key Features

- Low profile Mechanical keyboard
- Anodizing Aluminum top housing
- White backlit LEDs (reverse-mounted SMT)
- Plate mounted stabilizers
- Detachable TYPE C to TYPE C USB 2.0 cable
- Six RGB indicator LED, at the front right side of the keyboard
- Supports HY RF2.4GHz/Bluetooth module
- Working distance: within 10M, line of sight
- Rechargable 2600/4000mAh lithium battery, with NTC

#### **Technical Data**

[Electronics] [USB]

- o Input Voltage Range: 5V Max current consumption:
  - Single color backlit ON = less than 400mA
  - non-backlit OFF = 22mA

# [Wireless]


- o Lithium Battery Capacity: 2600/4000mAH optional
- o RF
- Working current: 6mA (no backlit)
- Sleeping current: 80uA
- o Bluetooth
- Working current: 6mA (no backlit)
- Sleeping current: 80uA

## [Keyboard Polling rate]

- o USB and RF2.4GHz = 1ms;
- o Bluetooth 5.0 = 132ms







Heng Yu Technology (HK) Limited <a href="http://www.hengyu-tech.com">http://www.hengyu-tech.com</a>

#### **Technical Data**

## [Others]

o Rechargeable 2400mAH Lithium Polymer Battery, fully charged = last for 4 Months\* (no backlit)

o Key strokes life: 50 million

o Key Travel Distance: 4mm

Storage temperature: -40°C to +55°C

o Operating temperature: 0°C to +45°C


o Operating humidity: 40% to 90%

o Dimensions: 440mm x 144mm x 29mm

o Approval and Compliance: FCC / CE / RoHS / REACH







\*without backlit turned ON, please refer to the Wireless mode tech. data

Heng Yu Technology (HK) Limited <a href="http://www.hengyu-tech.com">http://www.hengyu-tech.com</a>